MCZ GROUP

TECHNICAL DOCUMENTATION FOR LOCAL SPACE HEATERS ACCORDING TO COMMISSION REGULATION (EU) 2015/1186

Manufacturer Trademak Model Identifier Indirect heating functionality Direct heat output (space heat output) Indirect heat output (water heat output) CPR harmonised standard General description of the local space heater MCZ GROUP SpA SERGIO LEONI MARLENE L/A E no 9,0 kW kW EN 13240:2001/A2:200/AC:2007 Manually fed roomheater burning wood logs

Notified Body

ACTECO SRL (N.B. 1880) Via Amman 41, 33084 Cordenons (PN), IT

BLF = 1,45

Fuel	Preferred fuel (only one)	Other suitable fuel(s)	ηs [%]	EEI [%]
Log wood, moisture content ≤ 25 %	yes	no	70,8	107
Compressed wood with moisture content < 12 %	no	no		
Other woody biomass	no	no		
Non-woody biomass	no	no		
Anthracite and dry steam coal	no	no		
Hard coke	no	no		
Low temperature coke	no	no		
Bituminous coal	no	no		
Lignite briquettes	no	no		
Peat briquettes	no	no		
Blended fossil fuel briquettes	no	no		
Other fossil fuel	no	no		
Blended biomass and fossil fuel briquettes	no	no		
Other blend of biomass and solid fuel	no	no		

Calculations according to the council commission regulation (EU) 2015/1186 and 2015/1185 Characteristics when operating with the preferred fuel

$$EEI = (\eta_{S.on} \cdot BLF) - 10\% + F(2) + F(3) - F(4) - F(5)$$

$$\eta_{S,on} = \eta_{th,nom}$$

 $\eta_{s} = \eta_{s,on} - 10\% + F(2) + F(3) - F(4) - F(5)$

Observe the specific precautions for installation, assembly and maintenance indicated in the manual accompanying the product

Energy Efficiency Class A+

up to 2022

Characteristics when operating with the preferred fuel

Heat output			
Item	Symbol	Value	Unit
Nominal heat output	P _{nom}	9,0	kW
Minimum heat output (indicative)	P _{min}		kW

Auxiliary electricity consumption			
Item	Symbol	Value	Unit
At nominal heat output	el_max		kW
At minimum heat output	el _{min}		kW
In standby mode	el_{sb}		kW

$$F(4) = CC \cdot \frac{0.2 \cdot el_{max} + 0.8 \cdot el_{min} + 1.3 \cdot el_{sb}}{P_{nom}} \cdot 100[\%]$$

$$F(4) = 0.0\% \quad CC = 2.5$$

F(4) = 0,0 %

Permanent pilot flame power requirement			
Item	Symbol	Value	Unit
Pilot flame power requirement (if applicable)	P_{pilot}	N.A.	kW

$$F(5) = 0.5 \cdot \frac{P_{pilot}}{P_{nom}} \cdot 100[\%]$$
F(5) = 0.0

Contact details Name and address of the manufacturer MCZ GROUP SPA Via La Croce, 8 33074 Vigonovo di Fontanafredda (PN) Italy

Useful efficiency (NCV as received)			
Item	Symbol	Value	Unit
Useful efficiency at nominal heat output	$\eta_{\text{th,nom}}$	80,8	%
Useful efficiency at minimum heat output (indicative)	$\eta_{\text{th,min}}$		%

Type of heat output/room temperature control (select one)		
single stage heat output, no room temperature control	YES	
two or more manual stages, no room temperature control	NO	
with mechanic thermostat room temperature control	NO	
with electronic room temperature control	NO	
with electronic room temperature control plus day timer	NO	
with electronic room temperature control plus week timer	NO	

F (2) =

up to 2022

Other control options (multiple selections possible)	
room temperature control, with presence detection	NO
room temperature control, with open window detection	NO
with distance control option	NO

0,0 %

F (3) = 0,0 % up to 2022

Tel. +39 0434 599599 www.mczgroup.com contact@mcz.it

MCZ GROUP S.p.A Via La Croce, 8 - 33074 VIGONOVO di F.F.REDDA (PN) Tel. +39 8434 599599 - Fax +39 0434 528598 Cod. Fisc., P.IVA IT/0179 10 ous

Alessandro Di Bacco (Legal Representative)

Issue date: 27.06.2019

MCZ GROUP S.p.A. - Via La Croce n.8 - 33074 Vigonovo di Fontanafredda (PN) - Italia - Tel. +39 0434 599599 - Fax +39 0434 599598 - www.mcz.it - mcz@mcz.it Iscr. al Registro delle Imprese di Pordenone n. 01791730938 - Cod. Fisc. e P. IVA IT 01791730938 - R.E.A. Pordenone 104889 - Capitale Sociale € 10.000.000,00 i.v.